

L5 ANSWER 61 OF 575 CA COPYRIGHT 2004 ACS on STN
 AN 136:89781 CA
 ED Entered STN: 31 Jan 2002
 TI Polymer-cement slurry for decorative finishing of
 buildings
 IN Khrulev, V. M.; Plastunov, A. G.; Ottochko, O. D.; Kolesnikov, A. F.
 PA Novosibirskii Gosudarstvennyi Arkhitekturno-Stroitel'nyi Universitet,
 Russia
 SO Russ., No pp. given
 CODEN: RUXXE7
 DT Patent
 LA Russian
 IC ICM C04B026-02
 ICS C04B026-04; C04B028-04; C04B028-06
 CC 58-3 (Cement, Concrete, and Related Building Materials)
 FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	RU 2157796	C1	20001020	RU 1999-116199	19990727
PRAI	RU 1999-116199		19990727		
AB	The slurry comprises a mineral binder 25-35, filler (e.g., quartz sand, slag sand, or marble sand) 47-65, stabilized synthetic latex SKS 65GP 3.2-7 wt.%, and water in the balance. The mineral binder contains ground high-calcium fly ash 45-50, portland cement 30-40, and low fired clay powder 15-20 wt.%. The slurry exhibit better decorative properties, improved adhesion strength to concrete and compressive strength.				
ST	cement mortar fly ash clay latex decoration finishing				